### PH16W HP60 LED Bulb

DD0434S (Single) & DD0434P (Pair)

# DIODE DYNAMICS PERFORMANCE LIGHTING TECHNOLOGY



## **FEATURES**





- Replaces your factory-installed incandescent bulb
- Low power consumption with extra long life
- Plug and play, simple installation
- High-power CSP LEDs for maximum brightness in a small package
- Correct filament location for focused light output

## **GENERAL SPECIFICATIONS**

Function	Voltage Range	Current Draw*	Wattage	CCT/ Wavelength**	Lumen Output
Initial Output	9-16V	560 mA	7W	6000K	860 lm
Steady-State Output	9-16V	365 mA	4.5W	6300K	510 lm

<sup>\*</sup>Current Draw @13.2v \*\*+/-500 Tolerance

Color: Cool White

Connector Type: PH16W Base Connector LED Type/Count: 5W CSP Chips / 6 Total Operating Temperature: -40°C to 85°C Compliance Rating: J575 Durability Test

Length: 9" Width: 7" Height: 1"

Weight: 0.15 lbs

#### What's Included:

• One (1) or Two (2) PH16W HP60 LED Bulb(s)

All data and specifications are nominal values and may vary.


**PUBLISHED: 5-1-2020** 


## PH16W HP60 LED Bulb

DD0434S (Single) & DD0434P (Pair)





# **COLORIMETRIC SPECIFICATIONS**






# **PRODUCT DIMENSIONS**







**PUBLISHED: 5-1-2020**