Stage Series 2" Pro Yellow Flush LED Pod





FEATURES





- Modern TIR optics for the highest intensity on the market
- Backlighting in a brilliant amber color
- Durable powdercoated aluminum construction
- Integrated Deutsch-style connector
- Pin-fin heatsink design
- Designed, torture tested and assembled in USA

GENERAL SPECIFICATIONS

Optic	Peak Beam Intensity (Candela)	llluminance (lux @10m)	Measured Output (Lumens)	Raw Output (Lumens)	Output Color
Combo	24,000 cd	240 lux	1858 lm	2610 lm	Selective Yellow
Flood	650 cd	7 lux	1858 lm	2610 lm	Selective Yellow
Fog	7,500 cd	75 lux	1858 lm	2610 lm	Selective Yellow

Functions: Yellow Output with Amber Backlight

Voltage Range: 9-16V

Current Draw (amps @ 12.8V): 1.81A (output), 55.3mA (backlight)

Wattage: 23.1W (output), 708mW (backlight)

Connector Type: 4 Pin DT Connector

Driver Type: Integrated Driver

LED Type/Count: CREE XPL 4K/2 total, 3014 White/6 total **Compliance Rating:** J575 Durability Test, SAE-F J583, SAE-Y J581

Intrusion Rating: IP67 Weatherproof **Operating Temperature:** -40°C to 85°C

What's Included:

- One (1) or Two (2) Stage Series 2" LED Pods
- One (1) or Two (2) Deutsch-style wire pigtails
- One (1) or Two (2) Mounting brackets and hardware

Dimensions & Weight:

Length: 12.5" **Width:** 5" **Height:** 3.5" **Weight:** 1.15 lbs (single), 1.9 lbs (pair)

SKUs: Append "S" to the end of each SKU for single and "P" for pair


DD6433 Stage Series 2" Pro Yellow Fog Flush ABL DD6438 Stage Series 2" Pro Yellow Flood Flush ABL DD6735 Stage Series 2" Pro Yellow Combo Flush ABL

All data and specifications are nominal values and may vary.






COLORIMETRIC SPECIFICATIONS




PRODUCT DIMENSIONS




PHOTOMETRIC SPECIFICATIONS


Combo Optic Isolux




Combo Optic Perspective

Combo Optic Isocandela







Flood Optic Isolux



Flood Optic Perspective

Flood Optic Isocandela






PHOTOMETRIC SPECIFICATIONS

Fog Optic Isolux -30.0m -20.0m 0.0m 50.0m 100.0m 150.0m 200.0m 250.0m 300.0m

100.0 50.00 25.00 10.00 5.000 2.500 1.000 0.5000 0.5000 0.5000 1x

Fog Optic Perspective



Fog Optic Isocandela

